

检 测 报 告
TEST REPORT

报告编号

YNZKBG20220830013

Report No

项目名称

大理丰顺医疗废物处置有限公司 2022 年 8 月份自行监测

Name

委托单位

大理丰顺医疗废物处置有限公司

Client

项目地址

大理州大理市下关镇吊草村大风坝垃圾处理场以西

Address

样品类别

空气和废气

Type

编 制:

Compiled by

校 核:

Proofread check

审 核:

Inspected by

签 发:

Approved by

签 发 日 期:

Approved Date

李雪燕

董翔

检测专用章

2022 年 08 月 30 日

Y M D

云南中科检测技术有限公司

Yunnan Sino-soi Testing Tech. Co, LTD

报告日期

2022 年 08 月 30 日

Report Date

Y M D

声 明 Introduction

1.报告无“CMA 资质认定章”和检测单位“检测专用章”及“骑缝章”无效。

This report no seal on the perforation and CMA qualification certification seal and special seal for testing is invalid.

2.报告无编制人、审核人、签发人签名无效，报告经涂改无效。

This report without prepare people signature, audit staff signature, approver signature is invalid, The report by alter is invalid.

3.报告未经本机构批准，不得复制（全文复制除外）本报告或证书。

This report or certificate can't be copied (except in full) without the approval of the agency .

4.对委托人送检的样品进行检测的，检测报告对样品所检项目的符合性情况负责，送样样品的代表性和真实性由委托人负责；除委托方特别声明并支付样品管理费以外，所有样品超过标准或技术规范要求的时效性均不再留样。

If the sample submitted by the client is tested, the test report shall be responsible for the conformity of the items tested by the sample, and the client shall be responsible for the representativeness and authenticity of the sample submitted; Unless the entrusting party makes a special statement and pays the sample management fee, the timeliness of all samples exceeding the requirements of standards or technical specifications will not be retained.

5.委托方应对提供的检测相关信息的完整性、真实性、准确性负责。本公司实施的所有检测行为以及提供的相关报告以委托方提供的信息为前提，当委托方提供的信息可能影响结果的有效性时，本公司不承担由此引起的任何责任。

The entrusting party shall be responsible for the completeness, authenticity and accuracy of the testing related information provided. All testing behaviors and related reports provided by our company are based on the information provided by the entrusting party. When the information provided by the entrusting party may affect the effectiveness of the results, our company will not assume any responsibilities arising therefrom.

6.报告未经检测单位同意不得用于广告，商品宣传等商业行为。

This report without the consent of the testing organization shall not be used for advertising, advertising products such as business practices.

7.委托方如对本检测报告有任何异议，请于收到报告之日起十五日内向本公司提出申请，逾期不申请的，视为认可本检测报告。

If the client has any objection to the test report, please apply to the company within 15 days from the date of receiving the report. If the client fails to apply within the time limit, it shall be deemed to have approved the test report.

地 址： 云南省昆明经济技术开发区云大西路 39 号新兴产业孵化区 3 幢 3 层厂房
Address: The 3-story factory Building, 3 Building, Emerging Industry Incubation Zone, No.39 Yunda West Road, Kunming Economic and Technological Development Zone, Yunnan Province.

邮 编： 650500

Postcode ID:

电 话： 0871-63852008

Telephone No:

传 真： 0871-63802005

Fax No:

网 址： www.sttyznk.com

Website:

1.检测信息

表 1 检测信息

客户基本情况										
委托单位信息		单位名称	大理丰顺医疗废物处置有限公司							
		通讯地址	大理州大理市下关镇吊草村大风坝垃圾处理场以西							
		联系人	姚燮林			联系电话		13987202591		
受检单位信息		单位名称	大理丰顺医疗废物处置有限公司							
		通讯地址	大理州大理市下关镇吊草村大风坝垃圾处理场以西							
		联系人	姚燮林			联系电话		13987202591		
样品基本情况										
样品类别	样品名称	采样点位	采样频次		采样人员	采样时间	收样人员	收样时间	分析时间	样品状态描述
			天数	次/天						
空气和废气	有组织 排放废气	A1：焚烧炉废气排口	1	3	李光辉 陈昱潼	2022.08.18	吕梦林	2022.08.19	2022.08.19- 2022.08.29	——
	无组织 排放废气	A2：厂界上风向	1	3	王星宝 黄盛永	2022.08.18	吕梦林	2022.08.19	2022.08.19	——
		A3：厂界下风向 1#								
		A4：厂界下风向 2#								
		A5：厂界下风向 3#								

2.生产工单编号、检测类别、项目、方法、设备

表 2 检测分析及主要仪器设备一览表

生产工单编号	样品类别	检测项目	检测方法	检测和分析设备	仪器编号	分析人员	最低检出限
YNZKSC 20220802015	空气和废气	镉	HJ 657-2013 及修改单 空气和废气 颗粒物中铅等金属元素的测定 电感耦合等离子体质谱法	ICAP RQ ICP-MS	STT-YNZK-FX149	刘晨	0.008μg/m³
		镍					0.1μg/m³
		锰					0.07μg/m³
		铊					0.008μg/m³
		砷					0.2μg/m³
		铅		ZR-3260 自动烟尘烟气综合测试仪	STT-YNZK-XC481		0.2μg/m³
		锑					0.02μg/m³
		铜					0.2μg/m³
		铬					0.3μg/m³
		锡					0.3μg/m³
		汞	HJ 543-2009 固定污染源废气 汞的测定 冷原子吸收分光光度法（暂行）	F732-VJ 冷原子吸收测汞仪	STT-YNZK-FX173	刘晨	0.0025mg/m³
				ZR-3260 自动烟尘烟气综合测试仪	STT-YNZK-XC481		
				ZR-3710 双路烟气采样器	STT-YNZK-XC431		
		非甲烷总烃	HJ 604-2017 环境空气 总烃、甲烷和非甲烷总烃的测定 直接进样-气相色谱法	GC9790 II 型 气相色谱仪	STT-YNZK-FX063	徐仙丽	0.07mg/m³

3.检测结果

表 3-1 有组织排放废气检测结果表

NO.1

检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
镉	A1: 焚烧炉废 气排口	2022.08.18	YNZKSC 20220802015-A004	35	7.5	92.5	-0.06	11.52	14.5	6776	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.71×10 ⁻⁸
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.79×10 ⁻⁸
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.88×10 ⁻⁸
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.79×10 ⁻⁸
镍			YNZKSC 20220802015-A004		7.5	92.5	-0.06	11.52	14.5	6776	1×10 ⁻⁴ L	1×10 ⁻⁴ L	3.39×10 ⁻⁷
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	1×10 ⁻⁴ L	1×10 ⁻⁴ L	3.49×10 ⁻⁷
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	1×10 ⁻⁴ L	1×10 ⁻⁴ L	3.60×10 ⁻⁷
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	1×10 ⁻⁴ L	1×10 ⁻⁴ L	3.49×10 ⁻⁷
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 C _基 =C _实 ×（21-O _基 ）/（21-O _实 ），其中基准含氧量百分率为 11； 3.“检出限+L”表示检测结果低于方法检出限，进行计算时采用检出限值的二分之一。												

检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
锰	A1：焚烧炉废气排口	2022.08.18	YNZKSC 20220802015-A004	35	7.5	92.5	-0.06	11.52	14.5	6776	7×10 ⁻⁵ L	7×10 ⁻⁵ L	2.37×10 ⁻⁷
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	7×10 ⁻⁵ L	7×10 ⁻⁵ L	2.45×10 ⁻⁷
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	7×10 ⁻⁵ L	7×10 ⁻⁵ L	2.52×10 ⁻⁷
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	7×10 ⁻⁵ L	7×10 ⁻⁵ L	2.45×10 ⁻⁷
铊			YNZKSC 20220802015-A004		7.5	92.5	-0.06	11.52	14.5	6776	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.71×10 ⁻⁸
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.79×10 ⁻⁸
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.88×10 ⁻⁸
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	8×10 ⁻⁶ L	8×10 ⁻⁶ L	2.79×10 ⁻⁸
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 C _基 =C _实 ×（21-O _基 ）/（21-O _实 ），其中基准含氧量百分率为 11； 3.“检出限+L”表示检测结果低于方法检出限，进行计算时采用检出限值的二分之一。												

检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
砷	A1: 焚烧炉废气排口	2022.08.18	YNZKSC 20220802015-A004	35	7.5	92.5	-0.06	11.52	14.5	6776	2×10 ⁻⁴ L	2×10 ⁻⁴	6.78×10 ⁻⁷
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	2×10 ⁻⁴ L	2×10 ⁻⁴ L	7.20×10 ⁻⁷
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
铅			YNZKSC 20220802015-A004		7.5	92.5	-0.06	11.52	14.5	6776	2×10 ⁻⁴ L	2×10 ⁻⁴	6.78×10 ⁻⁷
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	2×10 ⁻⁴ L	2×10 ⁻⁴ L	7.20×10 ⁻⁷
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 $C_{基}=C_{实} \times (21-O_{基}) / (21-O_{实})$ ，其中基准含氧量百分率为 11； 3.“检出限+L”表示检测结果低于方法检出限，进行计算时采用检出限值的二分之一。												



检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
锑	A1: 焚烧炉废气排口	2022.08.18	YNZKSC 20220802015-A004	35	7.5	92.5	-0.06	11.52	14.5	6776	2×10 ⁻⁵ L	2×10 ⁻⁵	6.78×10 ⁻⁸
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	2×10 ⁻⁵ L	2×10 ⁻⁵ L	6.99×10 ⁻⁸
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	2×10 ⁻⁵ L	2×10 ⁻⁵ L	7.20×10 ⁻⁸
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	2×10 ⁻⁵ L	2×10 ⁻⁵ L	6.99×10 ⁻⁸
铜			YNZKSC 20220802015-A004		7.5	92.5	-0.06	11.52	14.5	6776	2×10 ⁻⁴ L	2×10 ⁻⁴	6.78×10 ⁻⁷
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	2×10 ⁻⁴ L	2×10 ⁻⁴ L	7.20×10 ⁻⁷
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	2×10 ⁻⁴ L	2×10 ⁻⁴ L	6.99×10 ⁻⁷
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 C _基 =C _实 ×（21-O _基 ）/（21-O _实 ），其中基准含氧量百分率为 11； 3.“检出限+L”表示检测结果低于方法检出限，进行计算时采用检出限值的二分之一。												

检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
铬	Al：焚烧炉废气排口	2022.08.18	YNZKSC 20220802015-A004	35	7.5	92.5	-0.06	11.52	14.5	6776	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.02×10 ⁻⁶
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.05×10 ⁻⁶
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.08×10 ⁻⁶
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.05×10 ⁻⁶
锡			YNZKSC 20220802015-A004		7.5	92.5	-0.06	11.52	14.5	6776	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.02×10 ⁻⁶
			YNZKSC 20220802015-A005		7.7	93.3	-0.05	10.95	14.3	6987	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.05×10 ⁻⁶
			YNZKSC 20220802015-A006		8.0	94.2	-0.05	11.47	14.1	7199	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.08×10 ⁻⁶
			平均值		7.7	93.3	-0.05	11.31	14.3	6987	3×10 ⁻⁴ L	3×10 ⁻⁴ L	1.05×10 ⁻⁶
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 C _基 =C _实 ×（21-O _基 ）/（21-O _实 ），其中基准含氧量百分率为 11； 3.“检出限+L”表示检测结果低于方法检出限，进行计算时采用检出限值的二分之一。												

检测项目	采样点位	采样日期	检测编号	排气筒高度 (m)	烟气参数						检测结果		
					流速 (m/s)	烟温 (℃)	静压 (kPa)	含湿量 (%)	含氧量 (%)	标干流量 (m³/h)	实测浓度 (mg/m³)	排放浓度 (mg/m³)	排放速率 (kg/h)
汞	A1：焚烧炉废气排口	2022.08.18	YNZKSC 20220802015-A001	35	7.9	93.8	-0.06	10.25	14.4	7214	1.14×10 ⁻²	1.73×10 ⁻²	8.22×10 ⁻⁵
			YNZKSC 20220802015-A002		7.7	94.2	-0.07	10.47	14.3	7006	1.10×10 ⁻²	1.64×10 ⁻²	7.71×10 ⁻⁵
			YNZKSC 20220802015-A003		7.5	94.6	-0.07	11.07	14.2	6771	1.17×10 ⁻²	1.72×10 ⁻²	7.92×10 ⁻⁵
			平均值		7.7	94.2	-0.07	10.60	14.3	6997	1.14×10 ⁻²	1.70×10 ⁻²	7.95×10 ⁻⁵
备 注	1.采样方法依据：GB/T 16157-1996 固定污染源排放气中颗粒物测定与气态污染物采样方法及修改单； 2.排放浓度折算公式为 $C_{基}=C_{实} \times (21-O_{基}) / (21-O_{实})$ ，其中基准含氧量百分率为 11。												

表 3-2 无组织排放监控点浓度检测结果表

检测项目	检测点位	采样日期	采样时段	样品编号	检测结果 (mg/m³)
非甲烷总烃	A2: 厂界上风向	2022.08.18	09:09	YNZKSC20220802015-A007	0.88
			13:11	YNZKSC20220802015-A008	0.92
			17:05	YNZKSC20220802015-A009	1.04
	A3: 厂界下风向 1#		09:20	YNZKSC20220802015-A010	1.63
			13:21	YNZKSC20220802015-A011	1.79
			17:16	YNZKSC20220802015-A012	2.63
	A4: 厂界下风向 2#		09:32	YNZKSC20220802015-A013	1.68
			13:35	YNZKSC20220802015-A014	1.82
			17:30	YNZKSC20220802015-A015	1.92
	A5: 厂界下风向 3#		09:46	YNZKSC20220802015-A016	3.22
			13:48	YNZKSC20220802015-A017	3.02
			17:40	YNZKSC20220802015-A018	2.90
备 注	采样方法依据：HJ/T 55-2000 大气污染物无组织排放监测技术导则。				

报告结束

附图:

大理丰顺医疗废物处置有限公司 2022 年 8 月份自行监测点位图



附件：

气象要素记录表

检测点位	采样日期	采样时段	气温 (℃)	气压 (kPa)	相对湿度 (%)	风向	风速 (m/s)	天气状况
A2: 厂界上 风向	2022.08.18	09:09	18.2	76.8	61.0	SW	1.2	晴
		13:11	23.7	76.2	48.3	SW	1.4	晴
		17:05	19.6	76.6	56.1	SW	1.5	晴
A3: 厂界下 风向 1#		09:20	18.0	76.7	60.8	SW	1.5	晴
		13:21	23.5	76.3	48.7	SW	1.6	晴
		17:16	19.4	76.5	56.5	SW	1.3	晴
A4: 厂界下 风向 2#		09:32	18.4	76.9	60.5	SW	1.4	晴
		13:35	23.3	76.4	48.6	SW	1.7	晴
		17:30	19.1	76.7	56.2	SW	1.2	晴
A5: 厂界下 风向 3#		09:46	18.5	76.7	60.9	SW	1.3	晴
		13:48	23.4	76.2	48.4	SW	1.5	晴
		17:40	19.3	76.4	56.3	SW	1.4	晴

